

Q-7 RGBW color LED wash blind strobe

Specifications	Optics	Light source LEDs expected lifetime Lens	2,000 x RGBW SMD LEDs (5,700K) 50,000 hours* 110° fixed
	Photometric	Light output Efficacy CRI	28,000 lumen (all LEDs on) 3,100 lumen (red) 6,300 lumen (green) 1,500 lumen (blue) 19,000 lumen (white) 60 lm/W Min. 80
	Features	Pan/Tilt	+ / - 90°
	Electrical	AC Power Maximum power consumption Typical power consumption Power factor	208 - 250 V Nominal 50/60 Hz 465 W (all LEDs on) 450 W (all LEDs on) 0.99 PF (230 V)
	Programming and Control	Protocol Setting and addressing DMX channels	USITT DMX 512 A Wireless DMX (LumenRadio) RDM Stand alone mode (programmable by RFID) Oled graphical display / 4 buttons Software upgradable via Uploader cable (P/N:83062011) 4, 6 or 8
	Physical	Dimensions (L x H x W) Weight Material Lens IP class	497 x 268 x 122 mm (19.6 x 10.6 x 4.8 in) 8.1 kg (17.9 lbs.) Aluminium Tempered glas front IP65
	Installation	Mounting Rigging possibilities Safety features	Any, but facing 100% down for permanent installation Stand bracket (included) or hanging (Omera Clamps included) Bottom mount for Safety wire
	Thermal	Temperature range, Operating Temperature range, Start-up Humidity (max.) Cooling	-10° - 40°C (-14° - 104°F) -10° - 40°C (-14° - 104°F) 98% Active, Forced air, temperature-regulated, low noise
	Connections	DMX data in/out Power	IP65 Neutrik HD locking XLR 5-pin cable 0.5m, for DMX in and out Power cable 0.5m with bare ends
	Conforms to	UL Std. 1573 2006/95/EC: Low Voltage Directive 2004/108/EC: EMC Directive RoHS2 Directive	EN 60598-1, EN 60598-2-17, EN 62471 EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3 2011/65/EU
	Included Items	Included Items	Floor Stand (incl. screws) 2 pcs Omega brackets Wireless DMX G4 antenna User Manual Neopren pouch
	Fixtures and Accessories	Fixtures Brackets Floorstand Barndoor Cables Flight case	Order no: 80030524 - Q-7 Color Flood Light Order no: 83060603 - BCC-2 Dual bracket Order no: 83060604 - BCC-4 Quad bracket Order no: 83060602 - Omega bracket Order no: 83060610 - Floorstand for P, Q and X series with 1/4-turn fasteners Order no: 83061123 - Accessory Holder X & Q Series Order no: 83061120 - Barndoor 4-way Order no: 83061121 - Barndoor 8-way Order no: 83061122 - Color frame Order no: 83062011 - SGM USB uploader cable Order no: 82051501 - Flight case for 4 pcs of P-5/Q-7/X-5

*(Figure provided by manufacturer and obtained under manufacturer's test conditions)